

VP Elite

The VP Elite: Production Braille embosser with high resolution Tactile Graphics

- The ViewPlus Elite is designed to fulfill high volume Braille production needs combined with high resolution tactile graphics
- Prints double-sided Braille in one pass, taking advantage of automatic print layout adjustments for enclosed tactile graphics
- The VP Elite uses continuous tractor feed paper up to 12-inch wide at a compact desktop machine size
- Provides a built-in **Ethernet** port for easy network installation

The **Braille dot** produced by ViewPlus embossers can be **adjusted in height**, allowing users to adjust to the individual sensibility of the reader's fingertip. This makes **extended Braille reading** more enjoyable, while maintaining **unsurpassed detail** in producing **tactile graphics**. The unique shape of the ViewPlus dot is proven to make Braille more durable, thus allowing **documents to last longer over time**.

ViewPlus solutions include **Windows printer drivers** that will allow embossing directly from Windows programs, utilizing the **same process as printing to mainstream color printers**.

What you see on the screen is what ViewPlus embossers will print, **representing the color spectrum from white to black in 7 different heights of the embossed dots**.

The **ViewPlus Elite** is also available with **InkConnect** (as shown in the picture on the bottom right), adding single-sided **black ink text and overprints on tactile graphics** to your Braille documents allowing sighted users to read along.

Though VP embossers are compatible with other Braille translation software, like Duxbury, and RTFC, ViewPlus also offers the **VP Tiger Software Suite (VP TSS)** for Braille translation, tactile graphics design and more. TSS allows the user to create Braille documents in standard Windows programs such as MS Word and Excel without needing to know Braille.



For more information please contact sales@viewplus.com or call 866-836-2184
www.viewplus.com

Specifications:

Print Speed: Up to 200 CPS

Printing Mode: double sided

Braille Dot Heights:
Adjustable in 3 heights

Tactile Resolution: 20 DPI

Tactile Graphic Dot Heights:
7 steps for color representation

Paper: Continuous tractor feed

Paper Width: 4 - 12 in
(101 - 305 mm)

Paper Weight: 30 - 140 lb
(50 - 230 gsm)

Connection: USB, Ethernet

Compatibility: Windows,
Mac OS 10.9

Height: 8.8 in (224 mm)
Width: 22.3 in (569 mm)
Depth: 13.8 in (351 mm)
Weight: 60 lbs (27,2 kg)

Recommended Temperature:
55 - 95 °F (13 - 35 °C)

Storage Temperature:
-4 - 158 °F (-40 - 70 °C)

Humidity: 20 - 80% RH
(non-condensing)

Energy Supply: 85 - 264 VAC
50/60 Hz (+/- 3%)

Standby: 22 W
Heavy Embossing: 235 W

**ViewPlus Elite
with InkConnect**

Differing dimensions:
Height: 10.7 in (272 mm)
Depth: 14.6 in (524 mm)